

Super Liquid Carbon

Application Guidelines

It is essential that oil spillages are treated with Super Liquid Carbon as soon as they occur, this will provide optimum results.

- Remove excessive spillage with absorbent paper
- Apply Super Liquid Carbon to the affected area
- Leave Super Liquid Carbon in place for 12-18 hours for optimum results
- This treatment can be repeated if necessary.

Application Rate

10 litres of Super Liquid Carbon in 50 litres of water per 500m²

WARNING



Health and Safety

Causes serious eye irritation

Causes skin irritation

Wash thoroughly after use.

Wear protective gloves/protective clothing/eye protection/protective footwear.

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Contains Cellulase. May produce an allergic reaction.

Safety data sheet available on request

CONDITIONS OF SUPPLY: No responsibility will be accepted by us or re-sellers for any failure in performance, damage or injury arising from their storage, handling, application or use of these goods. These conditions cannot be varied by our staff or agents whether or not they supervise or assist in the use of such goods.

Collier Turf Care Ltd, Drury Square, Beeston, King's Lynn, Norfolk, PE32 2NA

Tel: +44 (0) 1328 700 600

Web: www.collier-turf-care.co.uk