

Prestige Col-Mark Product Guide

The quality properties of the Prestige Col-Mark liquids allow fast, clean and easy dilution in to clean water. The formula is specifically designed to produce quality lines on grass. Prestige Col-Mark Premium is also suitable for use onshale as well as many other surfaces. The quick drying properties enable the liquid to create a durable bright line that is rain resistant.

Prestige Col-Mark Premium

Col-Mark Premium grade line marking liquid offers excellent brightness and performance on a wide range of surfaces. The recommended rates are dilute up to 1 part paint and 9 parts clean water. This is depending upon pitch conditions or line requirements.

- Free-flowing formula
- Outstanding White performance
- Suitable for multi surface types
- Ideal for spray marker machines
- Excellence performance over several weeks



Prestige Col-Mark Sport

Col-Mark Sport grade has been designed for use when a balance has to be struck between performance and cost. Ideal for a weekly marking of sport pitches. The recommended rates are dilute up to 1 part paint and 6 parts clean water. This is depending upon pitch conditions or line requirements.

- Outstanding white marking product
- Cost effective performance
- Ideal for municipal owned pitches
- For use with spray markers
- Excellence weekly performance



Prestige Col-Mark Transfer

Col-Mark Transfer is the perfect compound for the traditional box/transfer wheel marker. Can be used neat or diluted up to 1 part paint and 3 parts clean water. This is depending upon pitch conditions or line requirements.

- Cost effective in use
- High whiteness achieved
- Adheres to grass leaf
- Box/transfer wheel marker use only
- For frequent applications



Prestige Col-Mark Product Guide

Spray Marking Concentrate

How much concentrate is required at different dilution rates and pitch sizes.

Walking Speeds
Slow walk is 1.5mph
Medium walk is 2mph

Football Pitch Size
Small pitch 585meters
Medium pitch 665meters
Large pitch 745 meters

Small Pitch	1:4	1:5	1:6	1:7	1:8	1:9
Slow Speed	2.3L	2.0L	1.7L	1.5L	1.3L	1.2L
Medium Speed	1.8L	1.5L	1.3L	1.1L	1.0L	0.9L

Medium Pitch	1:4	1:5	1:6	1:7	1:8	1:9
Slow Speed	2.7L	2.2L	1.9L	1.7L	1.5L	1.3L
Medium Speed	2.0L	1.7L	1.4L	1.2L	1.1L	1.0L

Large Pitch	1:4	1:5	1:6	1:7	1:8	1:9
Slow Speed	3.0L	2.5L	2.1L	1.9L	1.7L	1.5L
Medium Speed	2.2L	1.9L	1.6L	1.4L	1.2L	1.1L

Products	WI	HP	WR	S	Dilution rates		Pack Size
					Wheel	Spray	
Prestige Col-Mark Premium	88.0%	95.5%	8	4	neat to 1:4	1:4 to 1:9	12.5 L
Prestige Col-Mark Sport	85.0%	91.0%	8	3	neat to 1:2	1:3 to 1:6	12.5 L
Prestige Col-Mark Transfer	65.0%	95.0%	35	3	neat to 1:3	N/A	12.5 L

The Measurements

Our Performance specifications are published in the following form:

1. WI - Witensess Index (Using international standard E313)
2. HP - Hiding Power (Using BS3900 Part D4)
3. WR - Wear Resistance (Using ASTM D4060)
4. S - Sedimentation (Using laboratory measurements)

